

Table of Contents

Startup config	3
<i>Push startup configuration to node(s)</i>	3

Startup config

Push startup configuration to node(s)

To push a startup configuration select the node(s) to push the startup configuration to by entering them in the Clients/Sites/Nodes list separated by comma, space, semicolon or newline or you can select the node(s) in question by selecting the client where the node resides, click the '»' button and thereupon select the desired node(s) and click the Next button.

Push Startup configuration

Xml (System) of NetYCE

Clients/Sites/Nodes list

items should be separated
(comma, space, semicolon, newline)

Add list

Clientcodes

- 9999
- 1973
- AMS
- SBB_BT
- SBB_BX
- Amsterdam
- CustX
- CustY
- ST_demo
- Vienna
- 5000
- FrieslandCam
- ESXi

Selected Nodes (49)

- lan-sw2
- lan-sw3
- lan-sw4
- p1
- p2
- p3
- p4**
- pe11
- pe12
- pe21
- pe22
- pe31
- pe32

Next

Choose the desired time the startup configuration should be pushed to the node(s), check the "Reload node after config push" checkbox if you want the node to reboot after the startup configuration has been pushed. Depending on the configuration of your NetYCE application you might need to supply a Change-id, click the *Schedule* button to schedule the startup configuration job(s)

Schedule:	<input style="width: 100px; height: 20px; border: 1px solid #ccc; border-radius: 5px; padding: 2px 5px;" type="button" value="tomorrow"/> at <input style="width: 20px; height: 20px; border: 1px solid #ccc; border-radius: 5px; padding: 2px 5px;" type="button" value="5"/> <input style="width: 20px; height: 20px; border: 1px solid #ccc; border-radius: 5px; padding: 2px 5px;" type="button" value="05"/> or <input type="checkbox"/> Now	<input style="border: 1px solid #ccc; border-radius: 5px; padding: 2px 10px;" type="button" value="Select all"/>
<input checked="" type="checkbox"/> Write Startup-config to node <input type="checkbox"/> Reload node after config push (<input checked="" type="checkbox"/> Check redundancy)		
<input style="border: 1px solid #ccc; border-radius: 5px; padding: 2px 10px;" type="button" value="Schedule"/> <input checked="" type="checkbox"/> Verbose		Change-id: <input style="width: 150px; border: 1px solid #ccc; border-radius: 5px; padding: 2px 5px;" type="text" value="C000xxxxxx"/>
<input style="border: 1px solid #ccc; border-radius: 5px; padding: 2px 10px;" type="button" value="Cancel"/>		

The result of scheduling a startup configuration for 1 node.

Push Startup configuration

Xml (System) of NetYCE

Scheduling the following jobs:

0728_0002 -- SCHEDULED -- Fri 29-Jul-2016 05:05:02 -- p4 Startup-config (no reload)

[Back](#)

From:

<https://labs-wiki.netyce.com/> - **Technical documentation**



Permanent link:

<https://labs-wiki.netyce.com/doku.php/menu:operate:tools:startup>

Last update: **2021/10/21 13:55**